

DURA SCRUBBER™



For truly clean wheels, there's no substitute for a good scrub. That's why Belanger's DuraScrubber™ offers "eight feet of clean" – a full 96-inch length to ensure that even the largest wheels get scrubbed through a complete rotation.

DuraScrubber™ features alternating 12" and 7" diameter crushed end tip bristles, to clean deep between wheel spokes, while also scrubbing the intricate latticework and foreground designs of today's complex OEM and aftermarket rim assemblies.

Because a wheel scrubber is called upon twice for every vehicle washed, DuraScrubber™ is built to last. Featuring a frame of double-wall aluminum and oversized pivot bearings and brush spindle bearings, DuraScrubber™ is engineered for extreme durability.

Available in hydraulic or electric drive, and requiring only the power connection and an air line, DuraScrubber™ also integrates quickly into your wash. This simple installation and choice of utility hookups offers you a true "set and forget" wheel cleaning solution.



| Belanger Incorporated Products Specification Sheet | | |
|--|--|------------------------------------|
|  | Belanger, Inc. reserves the right to revise specifications, features or designs, and to change or discontinue models at any time without notice or obligation. | |
| | BE0039 | Copyright 2009 Belanger, Inc. © |



Specifications

DuraScrubber™

REQUIREMENTS

Physical

| | |
|--------------------------------|---|
| Component Height | 14 1/2" |
| Maximum Tunnel Width Required | 14' 9" |
| Maximum Tunnel Length Required | 15' 6" (*May be installed underneath other compatible pieces of wash equipment) |

Utilities

Hydraulic Drive Option:

| | |
|-------------------------|---|
| Electrical Requirements | (1) one 110 VAC output from Controller to air panel |
| Hydraulic Lines | 3.5 GPM @ 1000 PSI; 1/2" supply and return lines |
| Pneumatic Requirements | 1/4" airline @ 90 PSI minimum 120 PSI maximum |

Electric Drive Option:

| | |
|------------------------|--|
| Electrical Requirement | (1) one 110 VAC output from Controller to air panel |
| 3 Phase Motor | 208V, 60Hz, 3.30 amp 230V, 60Hz, 3.30 amp 460V, 60Hz, 3.30 amp |
| Pneumatic Requirement | 1/4" airline @ 90 PSI minimum 120 PSI maximum |



Shown with available green powder-coated finish



Shown with standard aluminum finish